

## LA-UR-21-21997

Approved for public release; distribution is unlimited.

Title: Physics-Based Modeling of Space Weather During Large and Extreme Geomagnetic Storms

Author(s): Morley, Steven Karl

Intended for: Report

Issued: 2021-02-28

---


**Disclaimer:**

Los Alamos National Laboratory, an affirmative action/equal opportunity employer, is operated by Triad National Security, LLC for the National Nuclear Security Administration of U.S. Department of Energy under contract 89233218CNA000001. By approving this article, the publisher recognizes that the U.S. Government retains nonexclusive, royalty-free license to publish or reproduce the published form of this contribution, or to allow others to do so, for U.S. Government purposes. Los Alamos National Laboratory requests that the publisher identify this article as work performed under the auspices of the U.S. Department of Energy. Los Alamos National Laboratory strongly supports academic freedom and a researcher's right to publish; as an institution, however, the Laboratory does not endorse the viewpoint of a publication or guarantee its technical correctness.




# Physics-Based Modeling of Space Weather During Large and Extreme Geomagnetic Storms

PI: Steven K. Morley




Results from the Space Weather Modeling Framework. The color shows the current density. The cutaway volume shows the structure of the magnetosphere and bow shock. The increase in resolution towards the Earth can be seen in the bow shock, illustrating the multi-resolution grid. The configuration of the magnetic field, which determines particle access, is shown by the blue field lines. Temporal variations in the field and currents drives geoelectric fields on Earth's surface which presents a hazard to power transmission infrastructure.





**Results from a study of the impact of small-scale structure on Space Weather Modeling Framework predictions. Each panel shows the predicted magnetic perturbation (left column) and the rate-of-change of the magnetic field (right column) at Iqalut station. The top row includes all measured structure, while the rows below use successively filtered upstream boundary conditions. Reduced measurement cadence, or smooth “idealized” simulation drivers will lead to underestimates of the hazard to power transmission operators.**





**Results from a reconstruction of the geomagnetic storm that led to the failure of the HydroQuebec power grid in March 1989. The early part of the storm where the grid failure occurred is well reproduced in global activity measures (left). The panel below shows a map of predicted magnetic field rate-of-change near the time of infrastructure impact. The magnitude of response is similar to observations, but occurs at higher latitude than was seen in the actual event.**

